CHAPTER 7

CONCLUSIONS AND FUTURE WORKS

7.1 Introduction

This chapter presents the summary of this dissertation. The work that has been done in each chapter, the main contributions and also future works are presented in this chapter.

7.2 Conclusions

The chapter 3 of this dissertation presents the full order model of the Nine-Phase IPM machine in different stator connection. The modeling method used in this chapter is capable of predicting all details of the machine behavior. The first configuration is a single-star nine-phase IPM and it is simulated using all details of the machine geometry, including the full order functions of the turn and winding functions of the machine stator and the full order functions of the permanent magnet blocks and the airgap function. After generating the inductances of the machine, they are transformed to the rotor reference frame using the nine by nine transformation matrix to get the different components of the inductances. The generated inductances are used along with the permanent magnet flux linkages to model the machine. The model is simulated using MATLAB Simulink and the simulation results are presented.

The same method of the modelling was performed for symmetrical and asymmetrical triple-star nine-phase IPM machines. In this modellings, the full order functions of the turn and winding functions and the airgap functions are used to generate the inductances of the machine. After the inductances are generated they are transformed to the rotor reference frame. The resulting inductances in the rotor reference frame are used in the machine model to generate the model of

The design of the machine drive is done based on the minimum copper loss strategy. Based on this strategy and using Lagrange method, the copper loss is minimized while the machine is satisfying the load torque constraint. Using this method, the relationship between the q and d axis currents is derived.

The current regulators are also designed in this chapter for the machine axis in the rotor reference frame. The current regulators are designed based on the dynamic equations of the voltages of the machine axis.

The new position estimation method is also presented in this chapter along with the high frequency analyses. The essential signal processing method and the observer are also designed and presented. The designed drive and estimator are simulated with the full order model of the machine and the simulation results are presented. Finally using Tustin approximation, the drive is discretized and implemented in the prototype. The simulation results for constant volt/Hz and vector control drive are verified by the experimental results. The main contribution of this chapter is to get the positions from the non-torque producing channels so the machine does not generate any extra torque pulsations.

In the chapter 6 a sensor less drive is designed for the symmetrical triple-star nine-phase machine. After modelling the triple-star nine phase converter, the machine drive is designed using the average model of the machine which includes the coupling between the machine sets. The designed drive shows many complexities in the controller due to the couplings of the machines.

To remove the complexities, the decoupled model that was generated in the chapter 4 is used to design the drive. The drive is designed based on the minimum copper loss strategy and it has six current controller loops which are operating on the torque producing and non-torque producing channels of the machine. The reference currents of the torque producing channels are

The delay can be compensated using proper compensation methods that can be applied to the low pass filters.